

IBEX 156MHC-EIGER

570/575/580/585/590

IBEX HIGH EFFICIENCY MONOCRYSTALLINE SOLAR MODULES WITH HALF CELL TECHNOLOGY

0+5 Positive power tolerance (0+5W) guaranteed



High performance under low light.
Works at cloudy, rainy days



The monolithic perc cell structure technology (low resistance characteristics) is adopted (the maximum conversion efficiency of modules is up to 21.11%)



EXTREME WEATHER RATING. High-tech aluminium alloy frame, certified for high snow (5400 Pa) and wind loads (3800 Pa)



Reduced resistance between cells Less micro cracks, higher output power



SUPER STRONG FRAME. The overflow tank is waterproof with double layers. Aluminum frame enhances the mechanical load strength by 10%

IBEX 156MHC-EiGER 570-590

MONOCRYSTALLINE SOLAR MODULE

ELECTRICAL DATA AT STC

	570	575	580	585	590
Rated power P _{mpp} [Wp]	570	575	580	585	590
P _{mpp} range to	0/+5W	0/+5W	0/+5W	0/+5W	0/+5W
Rated current I _{mpp} [A]	13.29A	13.36A	13.43A	13.50A	13.57A
Rated voltage V _{mpp} [V]	42.89V	43.04V	43.19V	43.33V	43.48V
Short-circuit current I _{sc} [A]	14.18A	14.25A	14.32A	14.39A	14.46A
Open-circuit voltage U _{oc} [V]	50.88V	51.02V	51.15V	51.29V	51.42V
Efficiency at STC up to	20.39%	20.57%	20.75%	20.93%	21.11%
Application Class	Class A	Class A	Class A	Class A	Class A

Specification as per STC (Standard test conditions): irradiance 1000 W/m² | module temperature 25°C | Air Mass = 1.5

ELECTRICAL DATA AT NOCT

Power at P _{mpp} [Wp]	433.00	437.00	441.00	445.00	449.00
Rated current I _{mpp} [A]	10.61	10.65	10.69	10.73	10.77
Rated voltage V _{mpp} [V]	40.81	41.03	41.25	41.47	41.69
Short-circuit I _{sc} [A]	11.23	11.27	11.31	11.35	11.39
Open-circuit voltage U _{oc} [V]	49.02	49.25	49.47	49.69	49.91

NOCT (nominal operating cell temperature): irradiance 800 W/m² | Wind speed 1 m/sec | Ambient temperature | 20°C cell operating temperature 45 +/-2°C | Air Mass = 1.5

LIMITING VALUES

Max. system voltage [V]	1500V DC (IEC)
Max. return current [I]	20A
Operating Temperature	- 40 to +85°C
Max.tested pressure load [Pa]2	5400
Max. tested tensile load [Pa]2	3800

TEMPERATURE COEFFICIENT

I _{sc}	V _{oc}	P _{max}
0.05% /°C	-0.28% /°C	-0.36% /°C



SPECIFICATIONS

Number of cells	156 (6 x 26) 182x182
Dimensions	2465x1134x35 mm
Weight	30.5 kg
Front-side glass	3.2 mm tempered Low Iron Glass
Frame	Stable, anodised aluminium frame, black
Junction box	Split Junction Box (IP68)
Cable	4 mm ² , +900mm,-900mm Cust.Length
Diodes	3 Diodes
Plug-in connection	MC4 Compatible
Hail test (max. hailstrom)	Ø45mm 23 m/s 83 km/h

PACKING CONFIGURATION

Container	40 HQ	Pieces Per Pallet	30
Pallets Per container	18	Pieces per Container	540

The specifications and average values can vary slightly. Relevant is the corresponding data of the individual measurement. Specifications are subject to change without notice. Measurement tolerance depending on equipment: rated power +/- 3%, other values +/- 10%. All information given in this data sheet corresponds to DIN EN 50380. A potential light-induced degradation of the power after commissioning is not considered here. Further information in the installation manuals. 1 The specific warranty conditions are given under www.swissenergy-solar.ch | 2 Horizontal mounted | 3 Tolerance L/W = +/- 3 mm, H +/-2mm, the dimensions given in the order confirmation will be decisive | 4 Location and dimensions of holes on request



WARRANTY

20 YEARS
PRODUCT WARRANTY

30 YEARS
POWER WARRANTY

swiss solar